Poly Trio 8800 IP Conference Phone and PoE-enabled

Big room. Vast possibilities

Transform your large meeting rooms into havens of productive collaboration. With up to 20 ft/6 m of pickup range, quality audio, and Poly NoiseBlockAl technology, you can ensure the flow of ideas is uninterrupted.



*Product image may differ from actual product

Every word comes through

Catch every word and enjoy inflection without distracting background noise with Poly Acoustic Clarity technology.

All kinds of connections

Collaborate using audio, video, content, or all three. The Trio 8800 conference phone helps teams make decisions faster thanks to their choice of meeting preferences.

Platforms you trust

Connect to the platform you like best — or choose more than one with Poly hybrid registration.

Quality audio

Fill the room with Poly HD Voice 22 kHz quality audio and up to 20 ft/6 m of pickup range.

Mobile-friendly

Enjoy versatile audio connectivity from your preferred mobile devices (USB, Bluetooth®/NFC),¹

One-touch join

Start a meeting in seconds with one-touch join.

Supports multiple platforms

 $Maximize\ flexibility\ and\ investments\ with\ connectivity\ to\ multiple\ platforms\ simultaneously.\ Ideal\ for\ hybrid\ work\ environments.$

Datasheet



Poly Trio 8800 IP Conference Phone and PoE-enabled

Specifications







Display

Aspect ratio: 16:9

Native resolution: 720 x 1280 Panel technology: Color LCD

Display size (diagonal, metric): 12.7 cm (5")

Touch-enabled: Gesture-based, multi-touch capable touchscreen

Connectivity and communications

Wireless range: Up to 6.1 m

External I/O ports:

1USB 2.0 Type-A (for USB battery charging) 1USB 2.0 Micro-B (for USB audio device) 2 RJ-45 (10/100/1000BASE-TX Mbps)

Wireless technologies:

Bluetooth® 42

Wi-Fi network connectivity: 2.4-2.4835 GHz (802.11b, 802.11g, 802.11n HT-20) 5.15-5.825 GHz (802.11a, 802.11n, HT-20, 802.11n HT-40)

Battery

Power features

LAN IN: Built-in auto-sensing IEEE 802.3at, PoE Device (Class 4)
LAN OUT: Built-in auto-sensing IEEE 802.3af power sourcing equipment¹

User interface features

Languages

Arabic; Chinese; Czech; Danish; Dutch; English; French; German; Hungarian; Italian; Japanese; Korean; Norwegian; Polish; Portuguese; Romanian; Russian; Slovenian; Spanish; Swedish

Audio

Audio features:

Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and

background noise suppression

Comfort noise generation

DTMF tone generation (RFC 2833 and in-band)

Low delay audio packet transmission

Adaptive jitter buffers

Microphone type: Three cardioid microphones

Frequency response (microphone): 100 Hz to 22 kHz

Sensitivity (speaker): 92 dB

Audio codecs:

G.711 (A-law and µ-law)

G.722

G.722.1 G.722.1C

G.729AB

G.719 Polycom[®] Siren[™] 7

Siren™14

SILELL

OPUS

Environmental

Certifications and compliances: AS/NZS 609501; AS/NZS 62368117; Australia -AS/NZ4268; Australia A&C Tick; CAN/CSA C222 No. 609501-03; CAN/CSA C222 No. 62368114; CE Mark; CISPR22 Class B; EN 301 489-1, EN 301 489-3, EN 301 489-17; EN 61000-3-2; EN 61000-3-3; EN 62368-1; ETSI EN 300 328 v1.91; ETSI EN 300 330; ETSI EN 301 893 v1.71; FCC Part 15 (CFR 47) Class B; FCC Part 15.225; FCC Part 15.247; FCC Part 15.407; ICES-003 Class B; IEC 60950-1; IEC 62368-1; Japan Item (19); Japan Item (19)-3-2; Japan MIC/VCCI Class B; NZ Telepermit; ROHS compliant; RSS 247 Issue 1; UL 60950-1; UL 62368-1

Operating humidity range: 5 to 95%

Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit): $0 \text{ to } 40^{\circ}\text{C}$ / Storage temperature range (Celsius) / Storage temperature range (Fahrenheit): $-20 \text{ to } 70^{\circ}\text{C}$ / Energy star certified: ENERGY STAR* certified

Certifications

Certified collaboration software: Microsoft Teams; Skype for Business; Zoom

Special features:

Unicode UTF-8 character support

Applications supported

Management software:

Poly Zero Touch Provisioning

RealPresence Resource Manager (v. 10.1 or above) based provisioning

 ${\bf Polycom\,Device\,Management\,Service\,for\,Enterprise\,(PDMS-E)}$

Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management

Display features

On-screen virtual keyboard

Security

Security management:

802.1X Authentication and EAPOL Media encryption via SRTP

Digest authentication

Encrypted configuration files

HTTPS secure provisioning

Password login

Support for signed software executables

Support for URL syntax with password

Transport Layer Security (TLS)

Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2)

FIPS 140-2 compliant cryptographic module

Network

Supported network protocols:

DHCP VLAN discovery

LLDP-MED for VLAN discovery

FTP/TFTP/HTTPS server-based central provisioning

Manual or dynamic host configuration protocol (DHCP) network setup

QoS Support — IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP Time and date synchronization using SNTP

Provisioning and call server redundancy support

VoIP features:

IETF SIP (RFC 3261 and companion RFCs)

Poly Trio 8800 IP Conference Phone and PoE-enabled

Specifications







Headset and handset compatibility

Headset and handset compatibility: Bluetooth® headset compatibility

Telephony and call handling features

Telephony and call handling features:

 $Bundled\ with\ Polycom\ UC\ Software: Corporate\ Directory\ Access\ using\ LDAP$

Call timer and call waiting

Call transfer, hold, divert (forward), park, pickup

Called, calling, connected party information

Distinctive incoming call treatment/call waiting

Do not disturb function

Local configurable digit map/dial plan

Local five-way audio conferencing

Shared call/bridged line appearance

Visual Conference Management

Up to 3 lines (maximum one Skype for Business and Microsoft Teams)

Daisy-chain up to four

One-touch speed dial, redial and meeting join

Weight and dimensions

Product Primary Color: Black

Weight (metric): 950 g

Product Dimensions (metric): 38.3 x 7.5 x 33.2 cm

Package dimensions (metric): 48.3 x 11.5 x 39.4 cm

Package Weight (metric): 1970 g UPC number: 197497506389 Product number: 849A7AA

Warranty

Poly standard one-year limited warranty

What is in the box

Console

Network (LAN) cable-CAT-5E

USB Type-A cable

Cable wrap

Tactile overlay for improved accessibility

Setup sheet

Key Selling Points Footnotes

 $^{1}\,\text{Mobile}$ devices not included with the Poly Trio 8800 and are not sold by Poly.

Technical Specifications Footnotes

 $^{1}\,\mbox{Requires}$ full Class 4 power input on LAN IN for operation

